

LEYCO[®]-PROTECT 6

MICRO - POLYMER SEALING WAX FOR MACHINERY IN ALL TYPES OF HEAVY INDUSTRY



- Seals metal, lacquer and plastic surfaces
- Possesses a very good temporary corrosion protection
- Leaves a surface shine where it has been polished
- Skid-proof
- Facilitates surface cleaning
- Simple in application

LEYCO®-PROTECT 6 is used the chassis of trucks, cement silo trucks, ready-mix concrete mixers, construction machines, all machines and devices which are used in outside and industrial locations.

Furthermore LEYCO®-PROTECT 6 is used for sealing the back of metal formworks, preventing the adhesion of concrete and other contaminations. The slip hazard which is associated with the use of liquid release agents is removed.

LEYCO®-PROTECT 6 can be removed with LEYCO®-BLITZ .



LEYCO®-PROTECT 6

Product-No. 20.157

MICRO - POLYMER SEALING WAX

DESCRIPTION

LEYCO®-PROTECT 6 is a polymer micro sealing wax for the surface sealing of metal, lacquered and plastic surfaces. It forms a hard and skid-proof protective film, which protects against corrosion and which substantially simplifies cleaning. LEYCO®-PROTECT 6 can be polished up for a glossy appearance.

BENEFITS

- Very good temporary corrosion protection
- High gloss surface
- Substantial simplified cleaning
- Simple application

TECHNICAL DATA

Density: 0.8 g/ml
Color: yellowish
Flash point: 33°C
Form: liquid

APPLICATION

Before application test the suitability of Protect 6 on an inconspicuous area. Clean the surface that will be applied with Protect 6.

LEYCO®-PROTECT 6 should be applied in as thin and even a film as possible. A brush, hand sprayer or cloth is recommended for this.

Large surfaces will benefit from a sprayed application, whilst smaller areas can be coated with a cloth or brush.

The removal of the protective film can be made problem-free with LEYCO®-BLITZ. Conventional cleaning agents are not suitable for removing the Protect 6.

STORAGE

Protect from frost. Protected against fires in the carefully sealed container.

Minimum shelf-life 30 months.

HEALTH AND SAFETY INFORMATION

Inflammable Injurious to health, could cause lung damage if swallowed. Do not inhale vapours. If swallowed do not induce vomiting, immediately seek medical assistance showing them the label.

REMARK

Whilst information and/or specification contained herein is to the best of our knowledge true and accurate, and is based on many years experience, we cannot accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us, as we have no direct or continuous control over how or where our products are applied.

LEYDE-PRODUCTS are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale. 09.01.04

LEYCO CHEMISCHE LEYDE GmbH, Industriestr. 155, D - 50999 Cologne,

Tel.: +49 2236 - 9 66 00 0, Fax: +49 2236 - 9 66 00 11,

email: leycochem@leyde.com, internet: www.leyde.com